





 Smart Control
 Camera & Smart
 Smart
 Smart Electrical
 Smart Lighting

 Panel
 Door Lock
 Gateway
 Sensor
 Products
 Products

# **Contents**

Smart Control Panel

3-4

04

Camera &

Door Lock

13-14

**Smart Gateway** 

25-26

**Smart Sensor** 

29-30

05

Smart Electrical Products

37-38

Smart Lighting Products

51-52



# Specification

Screen size: 3.5 inch, 480\*320 Operating system: OS 5.0 (Base on Linux kernel) Protocol: Wi-Fi | Bluetooth Mesh | IR Gateway: Built-in Bluetooth Mesh&IR gateway Button: 3-gang button/relay Interaction mode: Touch screen Button | Voice | APP Installation: EU base | wall mounted | 100~240VAC







# **Smart Control Panel Mini**



Screen and buttons, use whichever you want



Built-in Bluetooth Mesh & IR gateway, supports all types of Bluetooth Mesh&IR devices



Support more than 110 device



Supports direct unlocking and video streaming on screen



# **TPA08-M3**

# Smart Control Panel Pro

- · Built-in Zigbee, Bluetooth Mesh gateway, directly connected to sub-devices, control is faster
- · Multi-modal interaction, it is a touch screen and Alexa voice assistant
- · Built-in two inner speaker and supports two wired speaker expansion

# Specification

Screen size: 8-inch, 1280\*800 Uplink Protocol: Wi-Fi (2.4G &5G), Ethernet Gateway: Zigbee & Bluetooth Mesh gateway System: Android

Mic: 2pcs

Speaker: 2\*2W inner speakers & 2\* wired speakers

Relay: 2 gang

Power Supply: AC100-240V Product size: 127.5\*233.5\*38mm

Voice: Alexa built-in

Installation: Wall mounted

# Specification

Screen size: 5 inch, 480\*854 Uplink Protocol: Wi-Fi (2.4G &5G)

Gateway: Zigbee System: Linux

Mic: 2pcs

Speaker: 2\*1.5W

Relay: 2 gang

Power Supply: AC100-240V

Product size: 72\*127.3\*10.5mm(base

excluded)

72\*127.3\*36.5mm(base included) Voice: Alexa Built-in

Installation: US base, wall mounted

# TPP05-Z(US)

# **Smart Control** Panel L

- · Built-in Zigbee & Bluetooth Mesh gateway, directly connected to sub-devices, control is faster
- · Multi-model interaction, it is a touch screen and Alexa voice assistant





Camera & Smart

**26°**C 24th Jun Mon

Leave mode

Smart Electrical Smart Lighting Smart Wearable and Smart

06:30

Home mode





# Smart control panel S



Support for almost all devices in the



Al voice interaction, "Alexa" small housekeeper



Customize intelligent home scenes and freely switch scene



Replacement Zigbee gateway to connect 100+ sub devices

# **Smart Control Panel MAX Series**



# TPA10-M2U

# **Smart Control Panel MAX**

- · Multi-modal interaction, support touch, button and App
- · Built-in multi-mode gateway, directly connected to Bluetooth and Zigbee sub-devices
- · One screen to control the whole family, view and control all devices in the home at any time
- · Integrated ultra-clear camera, easily initiate video calls and realize multi-screen interaction
- · One click to build intercom with outdoor station, talk and unlock conveniently

# Specification

Screen size: 10.1 inch, 1920\*1200 FHD Uplink Protocol: 2.4G Wi-Fi, Ethernet Gateway: Zigbee, Bluetooth Other interface: RS485 System: Android Memory: RAM 2GB, ROM 8GB Camera resolution: 5MP Mic: 2pcs Speaker: 2\*1.8W Sensor: temperature and humidity Relay: 2 gang Power Supply: 12V2A Product size: 259\*16\*13mm(base part not included) 259\*161\*39mm (base part included) Installation: US base, wall mounted



# Specification Screen size: 10.1 inch, 1920\*1200 FHD (USB TypeC, power line not included) alexa built-in Uplink Protocol: 2.4G Wi-Fi Product size: 259\*161\*13mm(base part not included) 259\*161\*39mm (base part included) Gateway: Zigbee, Bluetooth Installation: EU base, wall mounted (Mesh & Bluetooth LE) System: Android Camera resolution: 5MP Sensor: temperature and humidity Power Supply: 12V2A

# TPA10-M2E

# **Smart Control Panel MAX**



Multi-modal interaction, support touch, button and App control



One screen to control the whole family, view and control all devices in the home at any time



Built-in multi-mode gateway, directly connected to Bluetooth and Zigbee sub-devices



Integrated ultra-clear camera, easily initiate video calls and realize multi-screen interaction

Smart Control

Camera & Door Lock

Smart Gateway Smart

Smart Electrical Products

Smart Lighting

Smart Wearable and

# **Specifications**

Technical features: Bluetooth wireless technology, 2.4G Wi-Fi wireless technology, lithium battery Vifa SOUND sound, dynamic bass for enhanced listening

Input: Bluetooth wireless technology Speaker: 40mm x 1 paper cone NdFeB full-range unit, 46 x 65mm x 2 passive radiator Frequency Response: 70Hz-16KHz@-10dB Input voltage: USB, 5V

Auto power off: 20 minutes without operation

Built-in battery: Li-ion 9.25Wh Height/Diameter: 105mm/93mm

Net weight: 0.45kg





# Chat Mini



Voice Connect



Controlling devices in the home based



Set up automated scenario tasks based on LLM



Portable voice assistant and Bluetooth speaker



Vifa unique Danish tuning

# Specification

Specification: 100-240V~, 50/60Hz, 6A MAX Maximum load: single maximum 200W, total maximum 600W Wireless protocol: Wi-Fi, Bluetooth Operating Temperature: 0°C~40 Operating humidity: 5%-90%RH non-condensing Size: 86\*86\*11.5mm (Nonly panel) 86\*86\*51.4mm (with base) Net weight: 189g



TPR01-B

# **Smart Rotate Panel**



Intuitive Touchscreen and Knob Combination: Combining a high-resolution touchscreen with the rotary knob



Multi-Device Integration: Seamlessly connect and control a wide range of smart home devices



# Camera & Door Lock

Smart Control Camera & Panel

Door Lock

Gateway

Smart Electrical Products

Sensor

Smart Lighting Products

Smart Wearable and Smart Personal Care Health



### SC106-WL3

# ■ Cube Camera

- · HD 3 million real pixels, 102 degrees wide Angle lens
- Al power, supporting human form detection, pet detection, cry detection, abnormal sound detection and other intelligent algorithms

# Specification

1/3" Image Sensor Display Resolution: 2304\*1296 4mm Focal Length 10m IR Distance H.264/MJPEG Image Compression Support 2-way audio TF Card Storage: 128GB max Power Adapter: DC 5V/1A

# Specification

1/3" CMOS Sensor 2.8mm Forcal Length Display Resolution 2560\*1440 Support two way talk With integrated spotlight and IR light Support Color night vision Support cloud and local storage(Up to 128GB) Power Adapter: DC 5V 1A

## SC305-WBQ4

# **Cube Camera**

- 4MP HD Image ; 120° Wide Angle Lens
- · Support IP65, used indoor & outfoor
- · Al detection: Motion; Human; Sound; **Feature Detection**





# SC116-WZ4

# ■ P&T Camera

- 4 million pixels, 102 degrees wide Angle lens
- · Al power, supporting human form detection, pet detection, cry detection, abnormal sound detection and other intelligent algorithms

### Specification

1/3" Image Sensor Display Resolution: 1920\*1080/2560\*1440 4mm Focal Length 10m IR Distance H.264/MJPEG Image Compression Support 2-way audio TF Card Storage: 128GB max Power Adapter: DC 5V/IA



### SC316-WB4A

# ■ P&T Camera

- 4MP HD Image; 102° Wide Angle Lens
- · Support physical mask and one-button calling
- · Al detection: Motion; Human; Sound; Baby Crying; Pet and Human Feature Detection

### Specification

1/2.8" CMOS Sensor 4mm Forcal Length Display Resolution 2560\*1440 Support two way talk With integrated spotlight and IR light Support Color night vision Support cloud and local storage( Up to 128GB)

Wifi 6; Support 2.4GHz & 5GHz Power Adapter: DC 5V IA

### Specification

142°+103° Wide Angle Lens 1/3" CMOS Sensor 2.8mm + 4mm Dule lens Display Resolution 2560\*1440 Support two way talk With integrated spotlight and IR light Support Color night vision Support cloud and local storage(Up to 256GB) Power Adapter: DC 5V 1A

## SC319-WBR8

# **Dual Lens PT** Camera

- 2K+2K HD Video
- · Wifi 6; Support 2.4GHz & 5GHz
- \* Al detection: Motion; Human; Sound





# SC155-WQ3

# 2K Battery Camera

- 2K crystal clear picture quality
- 100% True wireless, no wiring required
- · Push notification when detecting Human
- · Compatible for solar panel

### Specification

2K HD Video, Resolution 2304\*1296 3.3mm Fixed Lens, FOV 120°(D) Support BLuetooth LE+Wi-Fi & Siren

Support Spotlight & Color Night Vision Support Human/PIR Detection & Area Settings

Built-in 5200mAh Lithium Battery, IP65 Design

# **Smart IP Camera Series**



# SC256-LS4

# 4G Battery PT Camera

- Support Color night vision
- · Built-in 9200mAh rechargeable lithium battery, paired with 5W solar panel
- · Support Al-powered Human and Vehicle detection and customizable activity zones
- · IP65 protection level, meeting the needs of multiple indoor and outdoor scenarios

### Specifications

2K+ resolution (4MP), With 6X dightal

1/3" CMOS Sensor

3.2mm Forcal Length Support two way talk

With integrated spotlight and IR light Support cloud and local storage( Up to

Qualcomm chipset 4G module, paired with two external antennas



2MP HD Video

2.8mm Fixed Lens, Support Night Vision Support Two-Way Video Call, 2.8 inch

Support Al Human/Sound Detection Support Smart Tracking

# SC316-WBA2

# P&T Camera with Screen

- · Built-in 2.8 inch Screen
- · Support Two-Way Video Talk
- · Push notification when detecting Human







# ■ Two Way Video PT Camera

- Support Two Way Video talk, with 2.8 inch screen
- · Support physical mask and one-button calling
- · Support Motion; Human; Sound Detection and Smart tracking

# Specifications

4MP HD Video 1/2.8" CMOS Sensor 4mm Forcal Length Support two way talk 10m IR Distance, Support Night Vision Support cloud and local storage (Up to 128GB) Wifi 6; Support 2.4GHz & 5GHz Power Adapter: DC 5V 1A 102° Wide Angle Lens

### Specification

2MP HD Video, Resolution 1920\*1080 2.5mm Fixed Lens, FOV 144°(D) Support Bird Detection & Squirrel Detection

Support 10000+Bird name recognition (not included) Built-in 5200mAh battery, IP65 Design

Built-in 3w Solar Panel Wood Bird Cage (Red Cedar), 3L Storage Capacity for Bird Food

# SF254-WC2

# Smart Bird Feeder

- Excellent Night Vision with 120° Wide
- · Support Bird Detection & Squirrel Detection and Drive
- · Built-in 3w Solar Panel
- · Wood Bird Cage (Red Cedar)



# SF254-WB2

# Hummingbird Feeder

- · Support intelligent bird identification, more than 300+ hummingbird identification
- · Support Siren alarm to repel squirrels
- · IP65 protection level, meeting the needs of indoor and outdoor multi-scenario

# Specification

2MP HD Video 1/3" CMOS Sensor 2.5mm Forcal Length; with 144 ° Wide Angle Lens Support cloud and local storage (Up to 128GB)

With integrated spotlight and Support Color night vision

Built-in rechargeable lithium battery power supply & solar power supply

# Specification

2K HD Video, Resolution 1536\*2048

2.5mm Fixed Lens, FOV 170°(D)

Support Motion/Human/Package Detection

Built-in 5200mAh Lithium Battery, IP65 Design Digital Chime (included) & Function Settling by APP Support Bluetooth LE + Wi-Fi & Tamper Alarm AC 8-24V Power Supply

# SC162-WCD3

# 2K Video Doorbell ▶

- · Indoor loud-volume chime linked with outdoor doorbell
- · See the visitor from head to toe with big FOV
- · Push notification when detecting Human & Package





# Specification

Mechanical KeysPower: 4\*AA+USB Charger Batteries Life Span: About 5000 times Working Temperature: -20-50°C Data Users: PIN Codes50 Cardss50 Fingerprints100 Door Thickness: 35-60mm Application: Wooden Doors Mortise: 60/70mm USLatchbolt



H13

# **Elegant Smart Handle**



App / Fingerprint / PIN Code / RFID Cards / Mechanical Key



### SOIB-TYBA

# ■ Smart DoorLock

- Screw slide design, Fit all Lock BodySizes, No Need Extra Re-drill
- Ultra-Slim 38mm, Wi-Fi Door Lock
- · Application, Suitable for All Mortisesand Doors
- · Multiple Ways to Unlock
- 38mm Lock for XingFa Aluminium Door

### Specification

Mechanical Keys Power: 4\*AAA+USB Charger
Batteries Life Span: About 5000 times
Working Temperature: -20-55\*C
Data Users: PIN Code+Cards 100
Door Thickness: 35-65mm
Support more thicker doors with special accessories
Applications: Wooden Doors,
Security Doors. Double-side Doors,
AluminumFramed Glass Doors
Mortise Standard: 3585

### Specification

9pcs/CTN (62.5x37.5x38.5mm) Foam packing One lock one box Weight: 2.0kG/pcs 5050# Mortise standard Support 5572Mortise 6085Mortise



# Elegant Smart Handle

- Smart Digital Fingerprint Lock
- · Work with proximity card
- · Aluminum alloy panel/handle
- · Black oxidation treatment
- Available for 6085,5572 mortise or single latch



Panel





# Specification

Storage Capacity: 100 pcs Materials: Aluminum Alloy

Surface treatment: Spray painting process Battery life: 12 Months (AAA) / 24 Months

Operating temperature: -20°C - 55°C

Working environment humidity: 40%RH ~ 85%RH Salt spray test: 96 hours

Installation: Hooks, self-tapping screws,

expansion screws

Supported Gateways: Bluetooth Gateway Certification: CE, FCC, RoHS, IP65





# **Lock Box**



Support management via App



Support Bluetooth unlocking, fixed password unlocking and temporary password unlocking



Compatible with AAA and CR123A batteries



Removable hooks to meet different usage scenarios

Smart Control Camera & Smart

Door Lock Gateway Sensor

Products

Smart Electrical Smart Lighting Smart Wearable and Smart

Personal Care Health Travel

# Integrated Products Brochure 23-24

# **Specifications**

Password: 100 Fingerprints: 50 Cards: 100 Battery: 2800mAh lithium battery Applicable door thickness: 35-55mm





# Specification

Palm Recognition: 50 Password: 100 Battery: 4\*AA

Applicable door thickness: 35-55mm







# **Smart Door Lock**



Unlocking method: fingerprint, password, RFID card, remote unlocking, mechanical key



Remote cat eye visual intercom





Internet access: Wi-Fi



# **Smart Door Lock**



Matter Protocol Over Thread Networking



Supports palm vein recognition unlocking, offering a more secure and convenient unlocking method compared to fingerprint recognition



Supports Home Key unlocking, allowing convenient unlocking through NFC with iphone or Apple Watch



Minimalist design with a hidden keyhole and an integrated handle 
 Smart Control
 Camera &
 Smart
 Smart
 Smart Electrical
 Smart Lighting
 Smart Wearable and
 Smart Panel

 Panel
 Door lock
 Gateway
 Sensor
 Products
 Products
 Personal Care Health
 Trave



# Smart Gateway







TYGWZB-01N

# Wireless Multimode Gateway

- Ultimate Price-to-Performance Home
- · Empowering local automation, Unfazed by external network disconnection

### Specification

Uplink communication: Wi-Fi Downlink communication: Zigbee, BLuetooth LE, Bluetooth Mesh, Beacon Bluetooth LE: Versatile connectivity includes Zigbee, Bluetooth Mesh, Bluetooth LE and Beacon Mesh

Max connection: 128 Power input: 5VIA Size: 62\*62\*15mm Product net weight: 30g Working temperature: -10~°C 45°C Working humidity: 10%~90%RH Storage temperature: -20°C ~60°C Storage humidity: 5%~90%RH

TYGWBS-02N

# Wireless Bluetooth Gateway

- Ultimate Price-to-Performance Home Gateway
- · Empowering local automation, Unfazed by external network disconnection

## Specification

Uplink communication: Wi-Fi Downlink communication: BLuetooth LE , Bluetooth Mesh, Beacon Mesh Bluetooth LE: Versatile connectivity includes, Bluetooth Mesh, Bluetooth LE and Beacon Mesh Max connection: 128 Power input: 5VIA Size: 62\*62\*15mm Product net weight: 30g Working temperature: -10~°C 45°C Working humidity: 10%~90%RH Storage temperature: -20°C ~60°C Storage humidity: 5%~90%RH

THP10-B-V2

# **Smart Bluetooth Gateway Pro**

- · High-performance Bluetooth Gateway for Smart Homes
- · Empowering local automation, Unfazed by external network disconnection
- · User-friendly signal strength diagnosis and fault replacement

# Specification

Uplink communication: RJ45, Wi-Fi Downlink communication: BLuetooth LE. Bluetooth Mesh, Beacon Mesh Max connection: 200 Bluetooth Mesh/16 /100 Beacon Mesh Power input: 5VIA Size: 90\*90\*23mm Product net weight: 75g Working temperature: -10~°C 55°C Working humidity: 10%~90%RH Storage temperature: -20°C ~60°C Storage humidity: 5%~90%RH





# Smart Wired Gateway Pro

- · The first Matter gateway in the industry to obtain alliance certification
- · It also has the roles of bridge, controller, and border router
- · It supports bridging of mainstream platforms such as Apple/Google/Samsung, as well as access to Matter devices from third-party categories

### Specification

Power Input: 5VIA Working Temperature: -10°C~ +45°C Working Humidity: 10%-90%RH Internet Port: 10/100Mbps Ethernet Product Size: 90mm\*90mm\*23mm Net Weight: about 74.5a Wireless Protocol: Zigbee, Thread





# **4G Gateway**

- · Metal material, reliable and durable
- · Multiple networks in one, free switching
- · Wireless networking, stable and reliable
- · External antenna for better distance
- · Optional power supply mode, easier to install and use

### Specification

Connection Protocol: Ethernet, Wi-Fi, 4G, Zigbee, Bluetooth Power input (choose one of two) Method 1: 5V2A Method 2: POE power supply Product size: 265\*240\*65mm (size without antenna installed) Product net weight: 480g Working temperature: - 10°C~+55°C Working humidity: 10%-90%RH (non-condensing) Storage temperature: - 20°C~+60°C Storage humidity: 5%-90%RH (non-condensing)



THP10-Z

# Wired Zigbee Gateway

- · Super network capacity, supporting 100+ devices Stable operation of 100+ devices at the same time
- · Zigbee 3.0 standard protocol self- organizing network Local linkage without fear of network disconnection

### Specification

Connection Protocol: Zigbee + Ethernet Number of device connections: 128 MAX Power input: DC5V/IA Product size: 90\*90\*23mm Product net weight: 74.5g Working temperature: -10°C ~55°C Working humidity: 10%~90%RH Storage temperature: -20°C ~60°C Storage humidity: 5%~90%RH



# Super Remote Hub

- · All-in-one: T&H sensor, remote control, scene switch
- · Real-time monitoring of T&H, auto- adjustment of air
- · Make traditional IR home appliances smarter, to link with a wide variety of scenes

### Specification

Product Size: 65\*65\*17mm Input: DC 5V/IA IR Distance: ≤10m IR Direction: Multidirectional Working temperature: -10°C~50°C Working humidity: ≤85%RH Connection mode: 2.4GHz 802.11b/g/n Smart Control Camera & Smart Smart Electrical Smart Lighting Smart Wearable and Smart Rangel Door Lock Gataway Sapage Products Products Personal Care Health Travel



# **Smart Sensor**

# Specifications

Model: HP320-W Working Voltage: 5VDC Wireless Protocol: Wi-Fi+Bluetooth LE Radar Frequency: 60GHz Detection Area: 6\*8 square meters (side mount); 4\*6 square meters (ceiling mount) Installation: Wall mounted/flat Working temperature and humidity: -10-45°C, 0-85%RH (non-condensed) Dimension: Φ80\*30mm



HP320-W

# Human Presence Sensor (Pro)



Ultra-high precision human presence partition detection, effectively eliminate interference, fine regional management



People Counting & Multi-person trajectory tracking



Fall detection & respiratory heart rate detection, good care aide

## **Specifications**

Model: HP210-Z

Working Voltage: 100-240V~ Wireless Protocol: Zigbee

Radar Frequency: 24 ~ 24.25GHz

Detection Area: projection diameter 6 meters (hanging

height 3 meters)

Installation: Ceiling flat mount/ceiling recessed mount Working temperature and humidity: -10°C-50°C, 0-85% RH, no condensation

Hole Size: 70-80mm

Product Dimension: Φ92\*38mm

Certifications: CE, RoHS, REACH

### HP210-Z

# Human Presence > Sensor

- · Human presence detection, detect motionless
- · The detection range can be adjusted to meet the space requirements of different sizes
- · Illumination detection, avoid linkage light on during the day, save energy consumption





# Presence Sensor(Plus)

· Selling point: Human existance partition detection, effectively eliminate interference; People counting, multi-person trajectory tracking; Illumination detection, avoid linkage light on during the day.

# **Specifications**

Operating voltage: 5V DC Communication mode: Zigbee Radar frequency: 24G HZ Detection area: 4\*6 square meters Installation: Wall mounted Operating temperature: -10-45°C, 0-85%RH (non-condensed) Product size:  $\phi 80$ \*H30mm



Smart Lighting



# MD100-Z, MD100-B

# PIR Motion Sensor

- · Human motion detection
- Battery level display
- Magnetic mounting, 360° adjustable detection angle

# **Specifications**

Working Voltage: 3VDC Wireless Protocal: Zigbee/Bluetooth Mesh Detection Distance: 7M Installation Height: 2m Battery Type: CR2450 Installation: Ceiling/wall mounted Working Temperature: -10°C~50°C Working Humidity: 10%~90% RH, no condensation Dimension: 46.2\*34.2\*12.9 mm Certifications: CE, FCC, RoHS, REACH

### Specifications

Working Voltage: 3VDC Wireless Protocal: Zigbee/Bluetooth Mesh Installation: 3M adhesive tape Battery Type: CR2032 Working Temperature: -10 °C~50 °C Working Humidity: 10%~90% RH, no condensation Dimension: 58\*58\*17mm

# EB101-Z, EB101-B

# SOS Emergency ▶ Button

- · One-button switch
- · Low power consumption
- · Smart scene automation





# WD100-Z, WD100-B

# Water Leak Sensor

- · Flood prevention, necessary at
- · Water leakage detection, real-time monitoring, remote push alarm information, scene

### Specifications

Working Voltage: 3VDC Wireless Protocal: Zigbee/Bluetooth Mesh Battery Type: CR2450 Working Temperature: -10 °C~50 °C Working Humidity: 10%~90% RH, no condensation Dimension: 62\*62\*17.5mm

### **Specifications**

Working Voltage: 3VDC Wireless Protocal: Zigbee/Bluetooth Mesh Battery Type: CR2450 Working Temperature: -10 °C~50 °C Working Humidity: 10%~90% RH, no condensation Dimension: 60x23x13mm&36x14x13mm

# DS100-Z, DS100-B

# Door and Window Sensor ▶

- · Real-time monitoring of door and window opening and closing status
- · Intelligent linkage, tool-free Installation





# TH101-Z

# Temperature and **Humidity Sensor**

· View the temperature and humidity on the device LCD screen

# **Specifications**

Wireless Protocal: Zigbee Response time: \$ 2s Measurement Accuracy: Temperature: ±0.3°C, Humidity: ±3% RH Response Time: ≤ls

Temperature Range: -10°C ~50°C Humidity Range: 0%~99% RH, no condensation

Dimension: 58\*58\*17mm

# **Matter over Thread Series**

Smart

Sensor

# Specifications

Battery Type: AAA\*2 Wireless Protocal: Thread Installation: 3M adhesive

Working Temperature: -10°C~50°C

Working Humidity: 10%~90% RH no condensation Dimension: 70\*35\*20mm

# Door and Window ▶ Sensor

- · Supports Matter protocol, offering a more flexible and convenient smart home experience.
- · Reliable performance with ultra-low power consumption
- · Ultimate experience, Supporting functions such as door opening reporting, time detection of door opening, statistics of door opening times and time-out linkage for door opening (Advanced functions require separate configuration).



# PIR Motion Sensor

- · Human motion detection
- · Ultra-low power consumption
- · Battery level display
- · Detection delay setting

# Specifications

Wireless Protocal: Thread Detection Distance: 6m Battery: AAA\*2 Installation: Ceiling/wall mounted Working Temperature: -10°C~50°C Working Humidity: 10%~90% RH, no condensation Dimension: 90\*45\*25mm Certifications: CE, FCC, RoHS, REACH

# Specifications

Battery Type: AAA\*3 Wireless Protocal: Thread Temperature Range: -10°C~55°C Humidity Range: 0%~99% RH, no condensation Response Time: ≤2s Measurement Accuracy: Temperature: ±0.3°C / Humidity: ±3% RH Dimension: 54\*54\*25mm

# Temperature and ▶ **Humidity Sensor**

- · Supports Matter protocol, offering a more flexible and convenient smart home experience.
- · Reliable performance with ultra-low power consumption.
- Ultimate experience, supports features such as a backlit display, storage for up to 100,000 temperature and humidity data points, gesture operation for temperature and humidity curves, and data export.



# Wi-Fi Series



# DS100-W

# Door and Window Sensor

- · Ultra-low power consumption with Wi-Fi, supports offline caching, reliable performance.
- · Rapid reporting, completes status reporting in as little as 1 second.

# Specifications

Battery Type: AAA\*2 Wireless Protocal: Wi-Fi 2.4GHz Installation Method: 3M adhesive

Working Temperature: -10°C~50°C

Working Humidity: 10%~90% RH, no condensation Dimension: 70\*35\*20mm



Working Voltage: 3VDC Wireless Protocal: Wi-Fi 2.4GHz Detection Distance: 6m Detection Angle: 110° Battery: 2\*AAA Installation: Ceiling/wall mounted Working Temperature: -10°C~55°C Working Humidity: 10%~90% RH, no condensation Dimension: 90\*45\*25mm

Certifications: CE, FCC, RoHS, REACH

MD100-W

# PIR Motion Sensor

- · Human motion detection
- · Ultra-low power consumption, 1S quick response
- · Battery level display
- · Detection delay setting



# Water Leak Sensor

- · Ultra-low power consumption with Wi-Fi, supports offline caching, reliable performance.
- · Rapid reporting, completes status reporting in as little as I second.

# **Specifications**

Battery Type: AAA\*2 Wireless Protocal: Wi-Fi 2.4GHz Installation: 3M adhesive tape Working Temperature: -10°C~50°C Working Humidity: 10%~90% RH, no condensation

Dimension: 70\*24\*20mm

### **Specifications**

Wireless Protocol: Wi-Fi+Bluetooth+433MHz RF Gateway Input: Type-C Sub-device Input: 3V, AAA\*2/CR2032 Accuracy: ± 0.3 °C, ± 3% RH Product Size: 105\*76\*13mm/72\*24mm/43\*43mm

# TH210-WR2/TH220-WB2

# Smart Thermo- ▶ hygrometer

- Data statistics & export
- · 4.5" screen real-time data display
- Over-limit alerts
- · Wide coverage & long battery life
- · Al Comfort Manager











# Smart Electrical Products

# Specifications

Voltage: AC90~250V, 50/60Hz Max Current: 15A Communication protocol: Wi-Fi 2.4G Certification: ETL, FCC



F3s202-NA

# Matter Smart Plug-NA



Matter over Wi-Fi



Matter Eco-System, multi-admin across multiple ecosystems



Support APP remote management / timer/schedule



Power monitoring (Optional)



# Fls203-EU

# Matter Smart Plug-EU

- Matter over Wi-Fi
- · Matter Eco-System, multi-admin across multiple ecosystems
- Support APP remote management / timer/schedule
- · Power monitoring (Optional)

### Specification

Voltage range: 220~240V 50/60Hz Max current: 16A Communication protocol: Wi-Fi 2.4G Certification: CE, RoHS

# Specification

Voltage range: 220~240V 50/60Hz Max current: 16A Communication protocol: Wi-Fi 2.4G Certification: CE, RoHS

# F2s203-EU

# **Bidirectional** measurement plug-EU

- · For Energy Monitoring of balcony power plant
- · Support APP remote management / timer/schedule
- · 2 Way Power monitoring



Smart

# **Smart Electrical Products**



# TSW-TIII

# Stick Logger

- · Support mainstream brands of inverters
- · Collects information on operating status and power generation, enhancing work efficiency and lowering management

### Specification

Interface support: RS485/RS232/TTL/ USB or other serial communications

# S16Pro

# Air-Conditioner Controller

- · Remote management Air-conditioner by App
- · Local touch panel control Airconditioner
- · Work with Alexa or google home to voice control
- Smart schedule

# Specification

Product Name: Smart Air Controller Input: DC 5V/IA Dimension: 80\*80\*16mm Infrared Frequency: 38kHz Temperature Measure Range: 0°C ~60°C Humidity Measure Range: 0%RH~99%RH Wi-Fi frequency: Wi-Fi 2.4G Display: LCD



### Specification

Color: Black or White Rated Voltage: AC 100V-240V Protocal: Zigbee Wiring: Neutral wire required Power capability: LED/Fluorescente Max 150W; incandescent Max 300W Product Size: 116\*70\*35 mm

### ZX-LP-US11W/B

# 1 Gang Wall Switch

- · On/Off control via touch button, App and
- · Schedule/Timer/Smart Scene
- · Work with Alexa, Google Home



# ZX-LP-US12W/B

# ■ 2 Gang Wall Switch

- · On/Off control via touch buttons, App and voice
- · Schedule/Timer/Smart Scene
- · Work with Alexa, Google Home

### Specification

Color: Black or White Rated Voltage: AC 100V-240V Protocal: Zigbee Wiring: Neutral wire required Power capability: LED/Fluorescente Max 150W; incandescent Max 300W Product Size: 116\*70\*35 mm

### Specification

Color: Black or White Rated Voltage: AC 100V-240V Protocal: Zigbee Wiring: Neutral wire required Power capability: LED/Fluorescente Max 150W; incandescent Max 300W Product Size: 116\*70\*35 mm

# 3 Gang Wall

- · On/Off control via touch buttons, App and voice
- · Schedule/Timer/Smart Scene
- · Work with Alexa, Google Home





DAC21C Series、DAC73C Series

# Smart Energy Meter

- Bi-directional energy metering, support two-way electric energy, and provide monthly and daily electricity consumption statistics
- · Built-in relay, remote control on/off
- · Monitor real-time voltage, current, power and

### Specification

Rate voltage AC: 85 ~ 275V for single phase, 3\*110/190V or 230/400V for three phase Rate Current/Frequency: 5(80)A / 45~65Hz Connection mode: Direct type Operating temperature: -25°C~+55°C Accuracy class: ±1% / 0.5%

### Specification

Rate voltage AC: 85 - 275V for single phase, 3\*110/190V or 230/400V for three phase Rate Current/Frequency: 5(100)A / 45-65Hz Connection mode: Current transformer type

Operating temperature: -25°C~ +55°C Accuracy class: ±1% / 0.5%

DAC11 Series、DAC73C-CT Series

# Smart Energy Meter

- LCD display
- Bi-directional energy metering, support two-way electric energy, and provide monthly and daily electricity consumption statistics
- Support 1 passive pulse output, 1 RS485 communication
- · Monitor real-time voltage, current, power and other information



# Specification

Rated voltage: AC 110/230V Rated frequency: 50Hz/60Hz Pole: 1P/2P/3P/4P Operating temperature: -25°C~+70°C Frame rated current: 100A Rated current: 6A/10A/16A/20A/25A/32A/40 A/50A/63A/80A/100A

· Mechanical Lifespan: 20,000 times

· Electrical Lifesoan: 10,000 times

AICB2SP 1P/2P/3P/4P Miniature

· Remote/local switch

· Accuracy level: level 1

· Compact Size with wide operating voltage

· Monitor real-time voltage, current,

power and other information

Circuit Breaker

AICB2SLP 2P/4P

# Miniature Circuit Breaker

- · Type A Leakage Protection, 30mA-300mA
- Remote/local on/off, support Leakage self-checking
- · Accuracy level: level 1
- · Monitor real-time voltage, current, power and others
- · Mechanical Lifespan: 20,000 times
- · Electrical Lifesoan: 10,000 times



# Specification

Rated voltage: AC 110/230V Rated frequency: 50Hz/60Hz Pole: 2P/4P

Operating temperature: -25°C~+70°C Frame rated current: 100A

Rated current: 6A/10A/16A/20A/25A/32A/40A/ 50A/63A/80A/100A

# Specification

Rated operating voltage Un: 100~240VAC, 50/60Hz Maximum monitoring current: 63A (1P+N) Type of measurement: U, I, Pf, P, E Accuracy class: Class 1

# **Smart Energy** Sensor

• SPM01 smart energy sensor is an monitoring device that can be installed in electrical power distribution board without occupancy of space at DIN rail.





# ■ Smart Energy Sensor

· SPM02 smart energy sensor is an monitoring device that can be installed in electrical power distribution board without occupancy of space at DIN rail.

### Specification

Rated operating voltage Un: 380~415VAC, 50/60Hz Maximum monitoring current: 63A

Type of measurement: U, I, Pf, P,E Accuracy class: Class 1

# Specifications

Wireless Protocol: Wi-Fi+Bluetooth Input: 100-240V ~ 50/60Hz Load: LED/CFL: 300W/110V Max Incandescent/Halogen: 600W/110V Max Sensor: Proximity to bright screen



PS121-W-US

# **Smart Scene Dimmer Switch**



Smart devices and scenes control



Supports wireless three/multi-way control and smart lighting



Customizable screen settings



ETL certified

# Specification

Wireless Protocol: Wi-Fi+Bluetooth Input: 100-240V ~ 50/60Hz Output: 16A Sensor: Proximity to bright screen



PS162-W-EU

# **Smart Scene Switch**



**Smart devices** 



Supports wireless two/multi-way control and smart lighting



On/off Control

# Renewable Energy Product





# Microinverter

- External antenna for relbiable Wi-Fi connectivity
- · Relilable IP65 for outdoor using
- · Adjustable power output on App

## Specification

Max. DC Output: 800W Max. Solar Input: 1000W MPPT Voltage Range: 30V-60V Ingress Protection: IP65



# Residential Single-Phase Hybrid Inverter

- · Robust backup power output capacity
- Wide range of MPPT voltage range
- Rebiable IP65 for outdoor using

### Specification

Power Output: 5kVA MPPT Voltage Range: 125V-550V Max. Solar Input: 7kW Ingress Protection: IP65 Max. Parallel Operation: 4 Units



### Specification

Expandable Capacity: 2240Wh - 6720Wh Max. Solar Input: 1,000W Max. DC Output: 800W Ingress Protection: IP65 Life Cycles: 6000 Cycles



URA-MESSI

# **Balcony Energy Storage**



Integrated MPPT, direct PV input



Home-ESS grade LFP battery



Easy installation and commissioning



Easy Plug & Play
MC4 Connectors



Specification

MPPT voltage: 180-850V Output power rating: 8KVA-15KVA Battery voltage: 125V-600V

Ingress Protection: IP65

# VEN8KHB-L1

# Residential Single-**Phase Hybrid Inverter**

- · Multiple models for various needs
- · Wide range of MPPT voltage, lower start voltage
- 150% overload capability for 10 seconds

### Specification

Power output rating: 3kW-8kW MPPT Voltage Range: 80V-500V DC/AC Input Ratio: 150% Ingress Protection: IP65 Operating Temperature: -25 °C-60 °C

# VEN15KHB-H3

# Residential Three-**Phase Hybrid Inverter**

- · Wide range of MPPT voltage, low start-up voltage to 125V
- 150% DC/AC ratio for larger solar system
- · Support diesel generator integration



# Low Voltage Energy Storage

- Intelligent BMS technology
- Modular design
- · Peak discharge current up to 200A

### Specification

Expandable Capacity: 5kWh - 30kWh Life cycles: 6000 Cycles Ingress Protection: IP65 Single Module Weight: 48kg

# Specification

Expandable Capacity: 7.68kWh -25.6kWh

Life cycles: 6000 Cycles Ingress Protection: IP65 Single Module Weight: 26.5kg

# URA-HVS2

# **High Voltage Energy** Storage

- · Intelligent BMS technology
- · One-person Installation
- · Modular design, flexible capacity



# SAT500F-P

# **Portable Power Station**

- · Easy portable for camping
- · 100W PD Fast Charging
- Smart App Control

# Specification

Capacity: 512Wh Max. / Peak Output: 500W / 1,000W Solar Charging power: 200W Weight: 7.5kg

# Specification

Expandable Capacity: 2240Wh - 6720Wh Max. / Peak Output Power: 2,400W / 4,800W Solar Charging Power: 1,000W Life Cycles: 4,000 Cycles Weight: 24kg

# SAT2200F-P

# Portable Power Station

- · Flexible capacity, outdoor or in home backup
- Powerful output for heave loads
- · Smart App Control





### SAT2200F-B

# **Extra Battery for Portable Power Station**

- · Small footprint, large capacity
- Max. 1C charge and discharge rate
- · Plug & play

# Specification

Capacity: 2240Wh Life Cycles: 4,000 cycles Weight: 20kg





# Smart Lighting Products

# **Smart Lighting Products**

Smart Lighting



# TY-HD06VCRH B7C-B

# **Highbay PIR** Sensor with zhaga

- · PIR Sensor for max 12M Height
- With Zhaga Book 18 Receptacle
- · Bluetooth Version

### Specification

Detection Angle <120° (Fresnel lens) Installation height: maximum 12M Input voltage/current: 10.5-15Vdc, 20mA Dimming signal: DIM 0-10V Connection mode: Zhaqa interface Working temperature: -25°C ~ +60°C Waterproof grade: IP65 Product warranty: 3 years

### Specification

Communication system NB-IoT/CATI/CAT M interface standard Zhaga joggle(Bottom 50.4mm \* 35mm high) input voltage DC 12V-18V maximum current ≤0.15A@+12V output signal 0-10V or PWM, either the DALI dimming needs to be customized major function Remote switching, dimming, timing, GPS, optical control, etc

### TY-NBLC03-DC, TY-C1LC04-DC, TY-CMLC03-DC

# Zhaga NB/Cat.1/ ▶ Cat.M controller

· LTE Cat.1, Cat.M, NB-IoT 3 wireless communication systems are optional, DC 12V power supply





### TY-NBLC01-AC, TY-CILC01-AC

# ■ NEMA NB/ Cat.1 controller

· AC power supply is suitable for the application of no auxiliary source output

### Specification

Communication system NB-IoT/LTE Cat.1 interface standard NEMA joggle (Bottom: 84mm \* 98mm high) input voltage AC 96-264V,50-60Hz load current ≤2A@AC220V output signal 0-10V or PWM, either the DALI dimming needs to be customized major function Remote switching, dimming, timing, GPS, light control, AC power metering, etc.

# Specification

Microwave frequency: 5.8GHz±75MHz Installation height: maximum 12m Input voltage/current: 10.5-15Vdc 40mA

Dimming signal: DIM 0-10V Connection mode: Zhaga interface Working temperature: -25°C ~ +60°C Waterproof grade: IP65 Product warranty: 5 year

# TY-HD06VCRH B7B-B

# Microwave > Sensor

- Microwave Sensor for max 12m Height
- · With Zhaga Book 18 Receptacle
- · Bi-level Dimmable, Daylight Priority
- · Bluetooth Version



# VITTEK (Siam Paragon Branch)

5th Floor Siam Paragon Shopping Center Unit K5A-13 Rama I Rd, Pathum Wan, Bangkok 10330 (66) 99-642-6653, (66) 94-553-9164

